



Laboratory Services Impression Evidence

These are management system documents utilized by ATF Laboratories. They are provided for informational purposes only. Sensitive or copyrighted information has been redacted. The documents are used in ATF Laboratories and not published with the intent of setting a policy or analysis standard for other laboratories. The inclusion of product names does not imply endorsement by ATF Laboratories.

These documents are current as of March 1, 2024. ATF management system documents are reviewed annually and revised as needed. For specific requests, submit a Freedom of Information Act (FOIA) request. Instructions on how to file a FOIA request are found at: www.atf.gov/resource-center/freedom-information-act-foia.

INDEX

ATF-LS-I1 Examination, Enhancement and Comparison of Impression Evidence

ATF-LS-I1 Appendix A - Processing

ATF-LS-I2 Documentation, Methodology, and Conclusions

ATF-LS-I3 Reporting



ATF-LS-I1 Detection and Collection of Footwear and Tire Tracks	ID: 1776 Revision: 5
Authority: Technical Leader	Page: 1 of 2
Original maintained by Quality Programs; copies are uncontrolled.	

1. Scope

1.1. There are a variety of processes, physical and chemical, used to detect and enhance Footwear and Tire Track impressions. The following is an overview of physical means; photography, and chemicals and reagents used. *Appendix A* contains more detailed information on specific chemical processes that may be used. If an examiner uses another formulation, commercially available kit, or another technique not mentioned in *Appendix A*, the formulation and a reference for that formulation shall be cited in the case record. These processes are intended to be used by personnel who have received the training necessary to employ these methods. Examiners can determine what processing procedures are appropriate or acceptable in casework.

2. Procedures

2.1. There are many ways to collect questioned and known footwear and tire tracks. The chosen procedure will depend on the nature and quality of the evidence.

2.1.1. *Best Practices for the Preparation of Test Impressions from Footwear and Tires. ANSI/ASB Best Practice Recommendation 021, First Edition, 2019.*

2.1.2. *Best Practice Recommendation for Lifting of Footwear and Tire Impressions, ANSI/ASB Best Practice Recommendation 049, First Edition, 2020.*

2.1.3. *Best Practice Recommendation for Casting Footwear and Tire Impression Evidence at the Crime Scene, ANSI/ASB Best Practice Recommendation 126, First Edition, 2020.*

2.1.4. *Best Practice Recommendation for Photographic Documentation of Footwear and Tire Impression Evidence, ANSI/ASB Best Practice Recommendation 050, First Edition, 2021.*

3. Instrumentation/Reagents

3.1. The following equipment is generally used in the mixing, applying, and storing of chemical reagents: beakers, glass trays, graduated cylinders, magnetic stirrer and stirring bar, scales, squirt bottles, and storage bottles. Processes should be applied in a fume hood, and appropriate protective equipment should be worn. Development may require the use of a low level oven or humidity chamber. An alternate light source or LASER may be necessary to visualize present/developed/enhanced impressions. Refer to a specific process for the reagents needed to mix stock and working solutions.



ATF-LS-I1 Detection and Collection of Footwear and Tire Tracks	ID: 1776 Revision: 5
Authority: Technical Leader	Page: 2 of 2
Original maintained by Quality Programs; copies are uncontrolled.	

3.2. Fingerprint powders, brushes, casting material, ink and ink roller, and lifting equipment and materials.

3. Safety Considerations

3.1. The procedures may involve the use of hazardous materials. It is the responsibility of the user to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use. Proper caution should be exercised and the use of personal protective equipment should be utilized to avoid exposure to dangerous chemicals. Consult the appropriate SDS for each chemical prior to use.

4. Quality Assurance and Controls

4.1. A control sample demonstrates the effectiveness of a reagent. The control sample will be a substance on an appropriate surface for testing the reagent. Control samples can be generated at the time of testing a reagent, or they can be produced *en masse* for routine testing. When impressions are developed on the control sample, it will be noted in the appropriate logbook, and for casework, in the case record. A positive reagent check is required for the working solution to be used in casework. If the reagent check is negative (no impression developed), a second control sample will be processed. If the second check is positive, record the results in the logbook and case notes. The working solution will not be used in casework if there is a second negative reagent check.

4.2. Working solutions are tested after preparation and prior to use – if it has been more than one day since the solution was prepared.

4.3. A control sample will be included in the cyanoacrylate fuming chamber every time evidence is processed.

4.4. The use of reagents may interfere with other forensic examinations such as: inks, paper, handwriting, indented impressions, body fluids, fibers, and paint. Examiners will be aware of how chemical/physical processing may affect another discipline's examinations.

4.5. Follow all federal, state, and local disposal regulations.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 1 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Amido Black

Amido black, or naphthalene black 10B, is a protein indicator particularly sensitive to those proteins present in blood. While other techniques for the enhancement of blood impressions are available, they may pose serious health hazards or display a reaction for short durations. Amido black is a safer, permanent procedure which can be used on porous or non-porous surfaces. Amido black does prevent subsequent serological examination and therefore may only be used after serological examination of the evidence. However, Amido black can be applied after cyanoacrylate fuming in many cases (see McCarthy and Grieve, 1989).

Successful staining of the impression will result in a blue-black colored impression.

Ways to Fix Blood Prior to Processing

1. Bake the item at 100° C for 30 minutes. Heat-sensitive items may be baked at a lower temperature for a longer time.
2. Submerge the item in the following solution: 20 g 5-Sulfosalicylic acid dissolved in 1000 ml distilled water for 3-5 minutes.
3. For dried blood, soak the item in methanol for at least 10 minutes.

Working Solutions

Amido Black (Methanol Base) Working Solution

Dissolve 2.0 g of amido black 10B in 100 ml of glacial acetic acid.
Add 900 ml of methanol and thoroughly mix.

1st Rinse

Mix 100 ml of glacial acetic acid with 900 ml of methanol.

2nd Rinse

Distilled (or tap) water.

Shelf life

Working Solution: indefinite

1st Rinse: mix as needed

Storage

Working Solution: dark glass bottle

Procedure

1. Place the amido black 10B working solution into a tray large enough to accommodate the item being processed.
2. Completely immerse the item being processed for 30 seconds to 1 minute. The solution should be agitated before as well as during the evidence application.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 2 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

3. 1st Rinse.
4. 2nd Rinse.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 3 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Ammonium Thiocyanate

Two dimensional impressions in dust or soil can be enhanced to make the impression more visible. Successful staining of the impression(s) will produce a reddish-brown colored impression (a reaction of iron with the dust or soil).

Working Solution

Combine 2.0 g ammonium thiocyanate with 90 ml acetone.
Slowly add 10 ml dilute nitric acid.

Shelf Life

Working Solution: 6 months

Storage

Working Solution: dark glass bottle

Procedure

1. Using a spray bottle, spray a fine mist onto the surface.
 - a. If the surface is non-porous, be sure not to over spray the substrate to prevent the solution from running.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 4 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Cyanoacrylate Ester (Superglue) Fuming

Cyanoacrylate vapor, ethyl or methyl cyanoacrylate, polymerizes with some latent impressions to produce a white residue. The contrast of developed impressions may sometime be improved by the application of fluorescent dyes and/or powders.

Working Solution

Liquid cyanoacrylate ester (superglue).

Shelf life

Working Solution: indefinite

Storage

Working Solution: original container

Procedure

1. Place evidence in the superglue chamber. When appropriate, hang items or place loose items in processing baskets.
 - a. If the chamber has UV capability, remove and secure the UV tubes.
2. Place enough superglue to cover the bottom surface of an aluminum dish then place it on the heating element in the superglue chamber.
3. Close and secure the chamber door.
4. Start the automatic cycle.
5. Remove evidence once the chamber door unlocks.
 - a. If the chamber has UV capability, replace the UV tubes and run a UV cycle in the chamber.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 5 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

LASER and Alternate Light Source Examination

Scientific instrumentation for the visualization of natural and chemical luminescence of latent impressions on physical evidence.

Procedure

1. Check instrument connection to electrical source.
2. Activate power and light source.
3. Select light source filter frequency (ALS).
4. Direct light wand towards evidence.
5. While wearing filter goggles, open the shutter and examine evidence for latent print luminescence. Close shutter when finished.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 6 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Leucocrystal Violet (LCV)

LCV is a reagent used to enhance and develop impressions deposited in blood. Successful staining of the impression will result in a violet colored impression. This reagent is sensitive to ultraviolet light and, within several days, the entire application area will turn violet – particularly if the background could not be rinsed. Developed impressions should be photographed as soon as possible.

Working Solution

Combine the following ingredients in the order listed and place on a stirring device for approximately 30 minutes.

1. 1000 ml hydrogen peroxide, 3%
2. 20 g 5-Sulfosalicylic acid
3. 7.4 g sodium acetate
4. 2.0 g LCV*

**If the LCV crystals are yellow instead of white, do not use them. This is an indication that the reagent is old and the resulting solution will not be effective.*

Shelf life

Working Solution: up to 30 days

Storage

Working Solution: dark glass bottle

Procedure

Spraying (most effective method of application)

1. Use the finest mist possible to spray LCV over the item.
2. Wait 30 seconds for development to occur.
3. Blot the area with a tissue or paper towel.
4. Repeat to improve contrast.
5. Do not leave processed item exposed to direct sunlight as photoionization may occur and result in unwanted background development.

Alternate application methods:

Dipping, or use of a squirt bottle.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 7 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Luminol

This reagent is best used on multi-colored or dark surfaces where other reagents will not produce an impression with sufficient contrast. A positive reaction will produce a blue white chemi-luminescence which appears almost immediately and fades rapidly. Spraying can be repeated during photography if necessary to maintain luminescence although this may result in degradation or washing away of the impression so care should be taken not to over spray the impression.

Working Solution

Dissolve 0.1 gram Luminol and 5.0 g sodium carbonate in 100 ml distilled water.
Immediately before using the mixture, add 0.7 g sodium perborate and mix completely.

Shelf life

Working Solution: use immediately

Storage

Working Solution: dark glass bottle

Procedure

1. Apply the working solution with a non-metallic aerosol sprayer.
 2. The working solution must be applied in total darkness to be visualized.
- NOTE:* This chemical does not have a fixative in it and the blood may run with continuous spraying.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 8 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Ninhydrin

Ninhydrin, or tri-keto-hydrindene hydrate, is an extremely sensitive indicator of alpha-amino acids, proteins, peptides, and polypeptides. The reaction produces a violet to blue-violet coloring of these substances and is effective with older deposits with even minute amounts of amino acids. While ninhydrin can be used on any surface, normally processing is confined to porous items which have not subsequently become water-soaked or do not contain inherent animal proteins.

Working Solutions

Alternate Petroleum Ether Formula

1. Dissolve 5.0 g of ninhydrin in 30 ml of methanol
2. Add 40 ml of isopropanol
3. Add 930 ml of petroleum ether

Acetone formula

Dissolve 6.0 g of ninhydrin in 1.0 L of acetone

Shelf life

Working Solution: up to 1 year

Storage

Working Solution: dark glass bottle

Procedure

Dipping (preferred method of application)

1. In a tray large enough to accommodate the evidence, pour enough working solution to cover all of the items.
2. Completely immerse each item to be processed in the working solution until the item is completely saturated, usually five seconds or less. The item can be manipulated using tongs or forceps.
3. Remove and allow the item to dry completely.
4. Place the item in the heat/humidity chamber at no greater than 80 degrees centigrade and between 60% and 80% relative humidity.
5. Check the item periodically to monitor the impression development. Care should be taken not to saturate the item with water vapor.

Alternate application methods

Brushing, spraying, or use of a squirt bottle.

Larger items that will not fit conveniently into processing trays should be painted with



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 9 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

the ninhydrin solution using a soft bristle brush. Two inch to four-inch nylon paintbrushes are adequate. Care must be taken to apply an even and thorough amount to all surfaces. Applying ninhydrin via aerosolized spray cans or squirt bottles to items of evidence is also permissible.

Additional formulas are available for use (commercial and manual preparation) and are widely accepted.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 10 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Physical Developer

Physical developer is a product devised specifically for the examination of wetted or water soaked porous items. This technique is a method which utilizes silver nitrate in an unstable ferrous/ferric redox solution in combination with a detergent solution. Although this technique was developed for water soaked items, it can be used on any porous item – water soaked or not.

Water soaked or wetted papers rarely contain sufficient amounts of amino acids or salts for effective examination with normal porous surface processes.

Physical developer requires special care and exact adherence to procedures. Some glassware and utensils must be dedicated to the technique and reagent contamination must be avoided.

Stock and Working Solutions

Solution 1 – Maleic Acid Prewash

1. Pour 1000 ml of distilled water into a 1500 ml beaker.
2. Add 25 g of maleic acid and a large magnetic stir bar rinsed with distilled water.
3. Stir with a magnetic stirrer until all solids are dissolved.

Solution 2 – Buffered Ferrous/Ferric Redox Solutions

1. Pour 1000 ml of distilled water into a 1500 ml beaker
2. Rinse a large magnetic stir bar with distilled water and place in the beaker.
3. Add the following chemicals in the order given making sure each chemical is fully dissolved before adding the next:
 - 30 g of ferric nitrate
 - 80 g of ferrous ammonium sulfate
 - 20 g of citric acid

Stir until all chemicals are dissolved and then stir an additional five minutes.

Solution 3 – Stock Detergent Solution

1. Pour 1000 ml of distilled water into a 1500 ml beaker containing a large magnetic stir bar previously rinsed with distilled water.
2. Add 3.0 g of n-Dodecylamine Acetate and stir with a magnetic stirrer.
3. Add 4.0 g of Synperonic N.
4. Stir for thirty minutes.
5. Pour the solution into a 1000 ml glass bottle, transferring any material not yet dissolved.

Solution 4 – Silver Nitrate

1. Pour 50 ml of distilled water into a 100 ml beaker.
2. Add 10 g of silver nitrate and stir for one minute.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 11 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

If using a magnetic stir bar, rinse with distilled water. The chlorine in tap water would combine with the silver nitrate and form a milky colored solution (silver chloride), rendering the solution unusable. Never use tap water for any of the working solutions.

Redox Working Solution

(must be combined in the order listed; mix in a beaker on a stirring device)

1. 1000 ml of Solution 2 (ferric redox)
2. 40 ml of Solution 3 (detergent)
3. 50 ml of Solution 4 (silver nitrate)
4. Mix for 3 – 5 minutes then place solution in a tray for processing.

Bleach Solution

1. The bleach solution is made by diluting household bleach at a ratio of 1:1 with tap water.

Shelf life

Solution 1: indefinite

Solution 2: indefinite

Solution 3: indefinite

Solution 4: indefinite

Redox working solution: mix as needed

Bleach solution: mix as needed

Storage

Solution 1: clear or dark glass bottles

Solution 2: clear or dark glass bottles

Solution 3: clear or dark glass bottles

Solution 4: dark bottles

Procedure

Step 1 – Maleic Acid Prewash:

1. Pour enough maleic acid prewash to cover the item that is being processed into a glass tray.
2. Immerse the item in the solution for at least five minutes, or until bubbles are no longer given off.

Step 2 – Redox Working Solution:

1. Pour enough Redox Working Solution to cover the items being processed into a glass tray.
2. Drain the items of excess prewash.
3. Immerse the items in the working solution and gently rock the tray.
4. Keep the items separated and be careful not to crease or handle the items extensively.
5. The processing time will vary from 5 to 15 minutes. It is important to monitor the development very closely to avoid over processing and obliteration of weaker impressions. Remove the item when optimum contrast is observed.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 12 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Step 3 – Water Rinse:

1. Fill a glass tray with enough tap water to cover the processed items.
2. Place processed items into the water rinse and agitate to remove the Redox Working Solution.
3. Continue until items are not releasing Redox Working Solution into the water.

Step 4 – Bleach Solution (optional – should be used when trying to improve the contrast of darker impressions):

1. Place the item in bleach solution for approximately 15 seconds.
2. Rinse the item under running tap water for at least one minute.

Step 5 – Drying:

1. Allow the items to air dry on a flat surface. The items may be blotted carefully to speed the drying process taking care with fragile evidence.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 13 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Potassium Thiocyanate

Two dimensional impressions in dust or soil can be enhanced to make the impression more visible. Successful staining of the impression(s) will produce a reddish-brown colored impression (a reaction of iron with the dust or soil).

Working Solution

Combine 15 g potassium thiocyanate with 120 ml acetone and 15 ml water.
Slowly add 8.5 ml dilute sulfuric acid.
Let the milky solution stand until it separates into two layers.
Decant the top layer off (and dispose of the bottom layer).

Shelf Life

Working Solution: 6 months

Storage

Working Solution: dark glass bottle

Procedure

1. Using a spray bottle, spray a fine mist onto the surface.
 - a. If the surface is non-porous, be sure not to over spray the substrate to prevent the solution from running.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 14 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Powders

Fingerprint powders and particulate developers are very fine particles with an affinity for moisture. Palmar sweat, grease, oil, and most contaminants that coat the surface of friction ridge skin possess sufficient moisture and viscosity to attract and bind the fine particles together. Contact between friction ridge skin and a non-porous surface will sometimes result in a transfer of the skin coating to that surface. The non-absorbency of the surface prevents penetration by the deposited moisture. All fingerprint powders and particulate developers are indiscriminate in adhesion to moisture. Surfaces coated with residue in addition to suspected latent prints will attract powders and particulate developers throughout the surface.

The most effective agent in terms of adherence to moisture, non-adherence to dry surfaces, particle size, shape, uniformity, and intensity of color is carbon. Black powders generally produce the best results. Other colored powders may be required due to the substrate encountered, but should be restricted to absolute necessity.

Magnetic powders are powder-coated, fine iron filings subject to magnetic attraction. These adhere to moisture to a lesser degree than carbon powders, but can be applied with less destructive force to the surface.

Particulate developers are substances which produce extremely fine particle residue upon burning. Materials with a high hydrocarbon content such as camphor, pine knots, or crumbled masking tape burn slowly and release soot in large quantities. Fine particulate carbon soot adheres extremely well to more viscous moisture while heat from the flame softens the residue. White or light colored soot may be produced by burning magnesium ribbon.

Most commercial black fingerprint powders have a high carbon base. According to the manufacturer's particular formula and production methods, the carbon base may be from a variety of sources, including lamp black, bone, or wood charcoal. Ground carbon alone cannot match the adhesion ability of fine particle carbon soot, but commercial powders contain milled carbon of highly uniform size and shape along with additional ingredients to preserve the milled condition and retard air moisture absorption.

No specific preparations are needed as the powders and materials being used are available commercially prepared.

DNA collection should always be a consideration when using powder. It is recommended to remove a small amount of powder from the container for use, and then throwing it away when finished. Single-use powders and brushes are commercially available, and should be used as needed in casework.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 15 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Shelf life
indefinite

Storage
original containers

Procedure

Nonmagnetic Powders

1. Remove the needed amount of powder from the storage container.
2. Dip the tip of the brush bristles into the powder.
3. Tap the excess powder onto the surface of the item being processed, and begin to brush.
4. Brush in the direction of developing ridges.
5. Slowly build powder onto ridges and stop when there is sufficient development.

Magnetic Powders

1. Remove the needed amount of powder from the storage container.
2. Place magna wand, with magnet engaged, into the powder.
3. Move the wand in a circular motion over the surface of the item being processed. The powder should touch the surface, never the wand.
4. Once development has occurred, release the attached powder back into the pile removed from the storage container.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 16 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Rhodamine 6G

Rhodamine 6G is a supplemental processing procedure designed to enhance faint or indistinct impressions developed by superglue fuming. Rhodamine 6G has an affinity for adhesion to polymerized latent impressions even at levels below visual observation. Excitation of Rhodamine 6G with the 488 nm, 510 nm, 514.5 nm, or 532 nm lines of the laser produces extremely bright fluorescence at about 550 nm.

Stock and Working Solutions

Petroleum Ether Carrier Formula

Stock Solution: dissolve 1.0 g Rhodamine 6G in 1000 ml of methanol.

Working Solution:

Mix in order:

- 3.0 ml stock solution
- 15 ml acetone
- 10 ml acetonitrile
- 15 ml methanol
- 32 ml isopropanol
- 925 ml petroleum ether

Methanol/Isopropanol Formula

Dissolve 0.1 g of Rhodamine 6G in 1000 ml of methanol or isopropanol.

Aqueous Formula

Dissolve 0.1 g of Rhodamine 6G in 1000 ml of distilled water.

Shelf life

Stock Solution: indefinite

Working Solutions: up to 6 months

Storage

Stock Solution: dark glass bottle

Working Solution: dark glass bottle

Procedure

1. Apply the solution to the item of evidence by using a squirt bottle or immersion.
2. Allow to dry completely.
3. Examine the item using a laser or other alternate light source.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 17 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

Small Particle Reagent (SPR)

Small particle reagent was devised and refined by the British Home Office as an effective procedure for processing wet surfaces. Both porous and non-porous, which are wet at the time of the latent deposit and those that become wet after deposit, seldom retain sufficient water soluble material for conventional processing methods. Non-porous items which have been allowed to dry offer some potential if the deposit contains non-water soluble oily matter. However, the drying process lessens the possibility of adequate adhesion for powders or particulate.

SPR is very effective in the secondary treatment of cyanoacrylate ester developed impressions by adhering to faint impressions generally better than powders and particulate. Molybdenum disulfide is produced in various particle sizes. Smaller particle size is the most effective.

Stock and Working Solutions

Surfactant Stock Solution

1. Dissolve 8.0 ml of Tergitol 7 in 500 ml of distilled water.
This will make approximately 10 L of working solution.

SPR Suspension Working Solution

1. Add 10 g of molybdenum disulfide to 5.0 ml of the Surfactant Stock Solution stirring slowly.
2. Continue to stir until the mixture is of a creamy consistency and free of any dry powder.
3. Stir in 900 ml of distilled water.

Shelf life

Stock Solution: indefinite

Working Solution: up to 6 months

Storage

Stock Solution: dark bottle

Working Solution: bottle

Procedure

Immersion Technique

1. Shake the working solution well and place in a shallow tray. Pour in enough solution to cover the item being processed.
2. Stir again before placing the item into the solution.
3. Place the item being processed into the solution.
4. Allow the item to remain in the suspension long enough for the molybdenum particles to settle on the item (approximately 30 seconds).
5. Turn the item and leave for an additional 30 seconds.
6. Continue, repeating steps 4 and 5 above until all surfaces of the item have been exposed to the solution.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 18 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

7. Place the item into a tray of tap water and rock until the excess SPR is removed.
8. Allow the item to dry.

Spray Bottle Application

1. Using a spray bottle, disperse enough SPR to cover the item.
2. Wash off excess SPR by running the item under a slow flow of tap water.
3. Allow the item to dry.



ATF-LS-I1 Appendix A - Processing	ID: 10040 Revision: 3
Authority: Technical Leader	Page: 19 of 19
Original maintained by Quality Programs; copies are uncontrolled.	

References

- Bodziak, William J., *Footwear Impression Evidence*, CRC Press, Inc., 1995
- Clay, W.E. "Fluorisol - The Solvent of Choice for Ninhydrin Detection of Latent Fingerprints." *Identification News*, vol. 31, no. 4, 1981, pp. 12-13.
- Home Office Centre for Applied Science and Technology (CAST). *Fingermark Visualisation Manual*. 2014
- Kimble, Gary W. "Powder Suspension Processing." *Journal of Forensic Identification*, vol. 46, no. 3, 1996, pp. 273-80.
- Lee, Henry C., Gaensslen, R.E. "Cyanoacrylate Fuming." *Identification News*, vol. 34, no. 3, 1984, pp. 8-14.
- Masters, Nancy E. "Rhodamine 6G: Taming the Beast." *Journal of Forensic Identification*, vol. 40, no. 5, 1990, pp. 265-70.
- McCarthy, Mary M., Grieve, David L. "Preprocessing with Cyanoacrylate Ester Fuming for Fingerprint Impressions in Blood." *Journal of Forensic Identification*, vol. 39, no. 1, 1989, pp. 23-32.
- Menzel, E. Roland. "A Guide to Laser Latent Fingerprint Development Procedures." *Identification News*, vol. 7, 1983, pp. 9-13.
- Menzel, E. Roland. "Detection of Latent Fingerprints by Laser-excited Luminescence." *Analytical Chemistry*, vol. 61, no. 8, 1989, pp. 557-61.
- Menzel, E. Roland. *Fingerprint Detection with Lasers*. Marcel Dekker, 2nd ed., 1999.
- Olson, Robert D. Sr. *Scott's Fingerprint Mechanics*, Charles C. Thomas Publisher Ltd, 1978.
- Phillips, Clarence E., et al. "Physical Developer: A practical and Productive Latent Print Developer." *Journal of Forensic Identification*, vol. 40, no. 3, 1990, pp. 135-47.
- Ramotowski, Robert, ed. *Lee and Gaensslen's Advances in Fingerprint Technology*, Elsevier Science Publishers, 3rd ed., 2012.
- Trozzi, Timothy et al. "Processing Guide for Developing Latent Prints." *FBI Publishing*, 2001.



ATF-LS-I2 Documentation, Methodology, and Conclusions for Footwear and Tire Track Examinations	ID: 10041 Revision: 4
Authority: Technical Leader	Page: 1 of 6
Original maintained by Quality Programs; copies are uncontrolled.	

1. Scope

- 1.1. These guidelines will ensure that Laboratory Services case records contain examination documentation that support the reported findings in a way that in the absence of the primary examiner, another qualified examiner in the discipline or supervisor could evaluate what was done and interpret the data.
- 1.2. These guidelines establish the methodology used in the examination of footwear and tire track impressions.
- 1.3. These guidelines establish the acceptable conclusions that can be reached from the comparison of footwear and tire track impressions.
- 1.4. The following are applicable to all case records generated by Laboratory Services examiners who examine footwear and tire track impression evidence.
 - 1.4.1. *United States Department of Justice Uniform Language for Testimony and Reports for the Forensic Footwear Discipline.*
 - 1.4.2. *United States Department of Justice Uniform Language for Testimony and Reports for the Forensic Tire Discipline.*

2. Procedure for Documentation

2.1. Inventory

- 2.1.1. The inventory of a questioned footwear or tire impression should be conducted prior to the inventory of a known footwear or tire.
- 2.1.2. Note collection information, if available (e.g., date of recovery, location, recovery methods).

2.2. Analysis

- 2.2.1. The analysis of a questioned footwear or tire impression shall be conducted prior to the analysis of a known footwear or tire in each step of the method when possible (e.g., general tread, size, wear, randomly acquired characteristics (RACs)).
- 2.2.2. Documentation of the analysis of footwear or tire impressions includes:
 - sample preparation;
 - date of collection;



ATF-LS-I2 Documentation, Methodology, and Conclusions for Footwear and Tire Track Examinations	ID: 10041 Revision: 4
Authority: Technical Leader	Page: 2 of 6
Original maintained by Quality Programs; copies are uncontrolled.	

examination quality photographs of questioned impression(s) and photographs of known(s);
processing techniques of questioned impression(s);
questioned impression(s):

- § quality;
- § class characteristics (e.g., manufacturing information, observed features);
- § interferences/limitations;
- § potential randomly acquired characteristics (RACs);

known footwear or tire(s):

- § condition of outsole or tread;
- § class characteristics (e.g., manufacturing information, observed features);
- § interferences/limitations;
- § RACs of use;
- § test impressions;
- § manner in which they were prepared;
- § matrix;
- § substrate.

2.2.3. Documentation shall correspond to the complexity of the examination and include markings of class characteristics and RACs of use where applicable.

2.3. Comparison

2.3.1. Documentation of comparison shall correspond to the complexity of the examination and should include markings of correspondence and non-correspondence, where applicable.

2.3.2. Documentation includes:

- method of comparison (e.g., side-by-side, overlay);
- class characteristics and RACs (if reproduced).

2.4. Evaluation

2.4.1. Documentation of evaluation includes:

- identifier of examiner;
- date;
- identification of items used;
- conclusion/interpretation reached, including justification.

2.5. Verification



ATF-LS-I2 Documentation, Methodology, and Conclusions for Footwear and Tire Track Examinations	ID: 10041 Revision: 4
Authority: Technical Leader	Page: 3 of 6
Original maintained by Quality Programs; copies are uncontrolled.	

2.5.1. Documentation of the verification corresponds to the complexity of the examination and includes:

- signature and date of verifying examiner;
- method of verification;
- items examined;
- conclusion/interpretation reached including justification.

3. Methodology

3.1. Analysis

3.1.1. Examination of questioned impression conducted to determine suitability for comparison. The quantity (how much of the impression is present) and the quality (clarity) of the detail are assessed and are dependent on a number of factors, including, but not limited to, the substrate, interferences, and the presence or absence of scales.

3.2. Comparison

3.2.1. The direct, side-by-side, and/or superimposed examination of a questioned impression to a known item to determine whether there is correspondence in class characteristics (e.g., outsole design, physical size, and wear) and/or randomly acquired characteristics.

3.3. Evaluation

3.3.1. Formulation of a conclusion based on the analysis and comparison of the questioned impression and known item.

3.4. Verification

3.4.1. Independent application of the ACE methodology by another qualified examiner.

4. Conclusions

4.1. Source identification (i.e., Identified)

4.1.1. 'Source Identification' is an examiner's conclusion that the known footwear/tire item made the questioned impression. This conclusion is an examiner's opinion that the known footwear/tire item and the questioned impression have corresponding



ATF-LS-I2 Documentation, Methodology, and Conclusions for Footwear and Tire Track Examinations	ID: 10041 Revision: 4
Authority: Technical Leader	Page: 4 of 6
Original maintained by Quality Programs; copies are uncontrolled.	

class characteristics (i.e., outsole design, physical size, and wear) and one or more randomly acquired characteristics with no meaningful differences, and the observed corresponding characteristic are sufficient such that an examiner would not expect to see the same combination of characteristics repeated in a different footwear/tire item.

4.1.2. The basis for a *source identification* conclusion is an examiner's opinion is that the observed corresponding characteristics provide extremely strong support for the proposition that the known footwear/tire item made the questioned impression and extremely weak support for the proposition that a different footwear/tire item made the questioned impression.

4.1.3. A *source identification* is the statement of an examiner's opinion (an inductive inference) that the probability that a different footwear/tire item made the questioned impression is so small that it is negligible.

4.2. Inclusion based on class and randomly acquired characteristics (i.e., Included)

4.2.1. 'Inclusion based on class and randomly acquired characteristics' is an examiner's conclusion that the known footwear/tire item probably made the questioned impression. This conclusion is an examiner's opinion that the known footwear/tire item and the questioned impression have corresponding class characteristics and one or more randomly acquired characteristics with no meaningful differences; however, there are limitations associated with the evidence that prevent a *source identification* opinion. For another footwear/tire item to have made the questioned impression, it would have to exhibit the same observed corresponding characteristics.

4.2.2. The basis for an *inclusion based on class and randomly acquired characteristics* conclusion is an examiner's opinion that the observed corresponding characteristics provide strong support for the proposition that the known footwear/tire item made the questioned impression and weak support for the proposition that a different footwear/tire item made the questioned impression.

4.3. Inclusion based on class characteristics (i.e., Included)

4.3.1. 'Inclusion based on class characteristics' is an examiner's conclusion that the known footwear/tire item could have made the questioned impression.

4.3.2. The basis for an *inclusion based on class characteristics* conclusion is an examiner's opinion that the known footwear/tire item and questioned impression have observed corresponding class characteristics with no meaningful differences.



ATF-LS-I2 Documentation, Methodology, and Conclusions for Footwear and Tire Track Examinations	ID: 10041 Revision: 4
Authority: Technical Leader	Page: 5 of 6
Original maintained by Quality Programs; copies are uncontrolled.	

There may be other footwear/tire items with characteristics that are indistinguishable from the known footwear/tire item that could have also made the questioned impression.

4.4. Inconclusive

4.4.1. 'Inconclusive' is an examiner's conclusion that no determination can be reached as to whether the known footwear/tire item could or could not have made the questioned impression.

4.4.2. The basis for an *inconclusive* conclusion is an examiner's opinion that there are limitations associated with the evidence that prevent an examiner from either including or excluding the known footwear/tire as a possible source of the questioned impression.

4.5. Support for exclusion

4.5.1. 'Support for exclusion' is an examiner's conclusion that the known footwear/tire item probably did not make the questioned impression. This conclusion is an examiner's opinion that the known footwear/tire item and questioned impression have different class characteristics and/or randomly acquired characteristics; however, there are limitations associated with the evidence that prevent an examiner from reaching *source exclusion* conclusion.

4.5.2. The basis for a *support for exclusion* conclusion is an examiner's opinion that the observed characteristics provide strong support for the proposition that a different footwear/tire item made the questioned impression and weak support for the proposition that the known footwear/tire item made the questioned impression.

4.6. Source exclusion (i.e., Excluded)

4.6.1. 'Source exclusion' is an examiner's conclusion that the known footwear/tire item did not make the questioned impression. This conclusion is an examiner's opinion that the known footwear/tire item and questioned impression have different class characteristics and/or randomly acquired characteristics.

4.6.2. The basis for a *source exclusion* conclusion is an examiner's opinion that the observed characteristics provide extremely strong support for the proposition that a different footwear/tire item made the questioned impression and extremely weak or no support for the proposition that the known footwear/tire item made the questioned impression.



ATF-LS-I2 Documentation, Methodology, and Conclusions for Footwear and Tire Track Examinations	ID: 10041 Revision: 4
Authority: Technical Leader	Page: 6 of 6
Original maintained by Quality Programs; copies are uncontrolled.	

5. References

- 5.1. Bodziak, W., *Footwear Impression Evidence: Detection, Recovery and Examination*, 2nd ed., CRC Press, Inc., 2000.
- 5.2. Bodziak, W., *Tire Tread and Tire Track Evidence*, CRC Press, Inc., 2008.
- 5.3. Cassidy, M., *Footwear Identification*, Canadian Gov. Pub., 1980.
- 5.4. McDonald, P., *Tire Imprint Evidence*, CRC Press, Inc., 1992.
- 5.5. Nause, L., *Forensic Tire Impression Identification*, RCMP.



ATF-LS-I3 Impression Reporting	ID: 10042 Revision: 4
Authority: Technical Leader	Page: 1 of 3
Original maintained by Quality Programs; copies are uncontrolled.	

1. Scope

1.1. This document establishes the acceptable reporting of conclusions for the comparison of footwear and tire track impressions. It is applicable to all Laboratory Services Forensic Science Laboratories.

2. Comparison conclusions

2.1. The following interpretation scale, in italics below, will be included as an appendix to comparative reports.

The following descriptions are meant to provide context to the opinions reached in this report. Not every type of conclusion may be applicable in every report.

Source Identification (i.e., *Identified*) is an examiner's conclusion that the known footwear/tire item made the questioned impression. This conclusion is an examiner's opinion that the known footwear/tire item and the questioned impression have corresponding class characteristics (i.e., *outsole design, physical size, and wear*) and one or more randomly acquired characteristics with no meaningful differences, and the observed corresponding characteristic are sufficient such that an examiner would not expect to see the same combination of characteristics repeated in a different footwear/tire item.

The basis for a source identification conclusion is an examiner's opinion is that the observed corresponding characteristics provide extremely strong support for the proposition that the known footwear/tire item made the questioned impression and extremely weak support for the proposition that a different footwear/tire item made the questioned impression.

A source identification is the statement of an examiner's opinion (an inductive inference) that the probability that a different footwear/tire item made the questioned impression is so small that it is negligible.

Inclusion based on class and randomly acquired characteristics (i.e., *Included*) is an examiner's conclusion that the known footwear/tire item probably made the questioned impression. This conclusion is an examiner's opinion that the known footwear/tire item and the questioned impression have corresponding class characteristics and one or more randomly acquired characteristics with no meaningful differences; however, there are limitations associated with the evidence that prevent a source identification opinion. For another footwear/tire item to have made the questioned impression, it would have to exhibit the same observed corresponding characteristics.



ATF-LS-I3 Impression Reporting	ID: 10042 Revision: 4
Authority: Technical Leader	Page: 2 of 3
Original maintained by Quality Programs; copies are uncontrolled.	

The basis for an inclusion based on class and randomly acquired characteristics conclusion is an examiner's opinion that the observed corresponding characteristics provide strong support for the proposition that the known footwear/tire item made the questioned impression and weak support for the proposition that a different footwear/tire item made the questioned impression.

Inclusion based on class characteristics (i.e., *Included*) is an examiner's conclusion that the known footwear/tire item could have made the questioned impression.

The basis for an inclusion based on class characteristics conclusion is an examiner's opinion that the known footwear/tire item and questioned impression have observed corresponding class characteristics with no meaningful differences. There may be other footwear/tire items with characteristics that are indistinguishable from the known footwear/tire item that could have also made the questioned impression.

Inconclusive is an examiner's conclusion that no determination can be reached as to whether the known footwear/tire item could or could not have made the questioned impression.

The basis for an inconclusive conclusion is an examiner's opinion that there are limitations associated with the evidence that prevent an examiner from either including or excluding the known footwear/tire item as a possible source of the questioned impression.

Support for exclusion is an examiner's conclusion that the known footwear/tire item probably did not make the questioned impression. This conclusion is an examiner's opinion that the known footwear/tire item and questioned impression have different class characteristics and/or randomly acquired characteristics; however, there are limitations associated with the evidence that prevent an examiner from reaching source exclusion conclusion.

The basis for a support for exclusion conclusion is an examiner's opinion that the observed characteristics provide strong support for the proposition that a different footwear/tire item made the questioned impression and weak support for the proposition that the known footwear/tire item made the questioned impression.

Source exclusion (i.e., *Excluded*) is an examiner's conclusion that the known footwear/tire item did not make the questioned impression. This conclusion is an examiner's opinion that the known footwear/tire item and questioned impression have different class characteristics and/or randomly acquired characteristics.



ATF-LS-I3 Impression Reporting	ID: 10042 Revision: 4
Authority: Technical Leader	Page: 3 of 3
Original maintained by Quality Programs; copies are uncontrolled.	

The basis for a source exclusion conclusion is an examiner's opinion that the observed characteristics provide extremely strong support for the proposition that a different footwear/tire item made the questioned impression and extremely weak or no support for the proposition that the known footwear/tire item made the questioned impression.

3. References

- 3.1. *United States Department of Justice Uniform Language for Testimony and Reports for the Forensic Footwear Discipline.*
- 3.2. *United States Department of Justice Uniform Language for Testimony and Reports for the Forensic Tire Discipline.*